EZee Life™

4" Raised Toilet Seat

Model: CH2020

EZee Life™ Products
34 Futurity Gate, Unit 15
Concord, Ontario L4K 1S6

Information

Warranty:

Ezee Life™ products carry a one year warranty against manufacturing defects, faulty materials and workmanship.

In the event of a defect covered by this warranty, we will, at our option, repair or replace the item. Please contact your supplier/dealer for assistance should a defect become apparent.

The warranty does not extend to consequential costs resulting from the fault or defect in the product, in particular freight and travel costs, loss of earnings, expenses or other expenses which may occur.

The warranty does not cover normal wear and tear resulting from normal use or damage caused by accident, misuse, negligence or improper installation or assembly.

The vendor/manufacturer will not accept responsibility for any damages or injury caused by misuse, negligence or non-observance of the instructions supplied.

Specifications:

Weight capacity:	220 lbs
Color:	White
Seat Height:	4"
Seat Width:	15"
Seat Depth:	15"
Weight:	4 lbs

Important Information:

1. Read the instructions before assembling; do not use this product without proper instruction from a professional.

2. If components are damaged or missing, contact your dealer immediately.

3. Do not use raised toilet seat unless it fits tightly on toilet bowl

4. Always check for secure fit of raised toilet seat.

5. This product has a maximum user weight of 220 lbs.

Intended Use:

Toilet Aides increase independence when using the toilet, particularly for impaired movement.

Installation Instructions:

- Raise the toilet seat that is attached to the toilet. The raised toilet seat will be placed on the toilet bowl rim.

- Place the raised toliet seat upside down on a flay surface and slip one of the “L” shaped brackets into one of the slots in the side of the seat (A). Push lightly on the bracket and run the knobclockwise until the thread engages.

Information

- Turn the knobs until the brackets are farther apart than the width of the toilet bowl.
- Turn the seat over and place it on the rim of the toilet bowl so that the the narrow cutout is at the front and the brackets are near the back of the bowl. Position the seat with the front lip on the seat against the outside front of the bowl.
- Tighten both brackets until they are snug against the bowl.
- The raised toilet seat should be level and fit tightly.
- Regular checks of the brackets should be made to ensure the raised toilet seat remains secured to the bowl. Spare Brackets are available if required.

Care and Cleaning:

- All parts are can be cleaned wiht soap and hot water (up to 195°F / 90°C).
- The adjusting screws can be popped out of the brackets for cleaning.

Cautions:

Do not hold onto the seat as a support when getting on and off the toilet.

Be sure the raised toilet seat is securely in place before putting weight on it.

Imported & Distributed by:

Factory Direct Medical

34 Futurity Gate, Unit # 15

Concord Ontario L4K 1S6

Local: 416-739-8393

Toll Free: 855-235-2400